MIRAI

experience the future

DTL-522P100

22” / 56 cm LCD TV

HDMI

HD ready

1000 : 1 Contrast

6,5ms Ultra Fast

ChroMAX circuitry

DUAL SCART

MIRAI

experience the future

DTL-522P100

22” / 56 cm LCD TV

Screen Size	466.56 (H) x 291.6 (V)
Aspect Ratio	16:10
Pixel Pitch	0.5190 (H) x 0.5190 (V)mm
Panel Resolution	1440 x 900
Brightness	400 cd/m^2
Contrast Ratio (typ.)	1000 : 1
Response Time (typ.)	6.5 ms
Viewing Angles (typ.)	176^0 (H) / 176^0 (V)
Display Color	16.7M
Tuner System	PAL, SECAM, NTSC Video
Standard TV	B/G, D/K, I, L/L’
Control Panel	Power (On/OFF), Source Select (SCART 1/SCART 2/TV/AV/SV/YPbPr/VGA/ HDMI), Menu (OSD) Operation, Channel Up, Channel Down, Volume +, Volume -, IR Receiver
Terminal I/O	Full SCART - SCART 1: CVBS/RGB(IN), TV(OUT), SCART 2: CVBS(IN), AV/TV(OUT) VGA Input, PC Audio In (for VGA), HDMI, Headphone Output, Component Video (YPbPr) over VGA input, -R/L Input, Composite Video-R/L Input
Support Timing	480i / 480p / 576i / 576p / HDTV (720P / 1080i)
Speaker	3W x 2
User Controls	Contrast, Brightness, Back Light, Saturation, Colour Temp, Red, Green, Blue, White Balance, Picture Mode, DCI, LTI, Aspect Ratio, Auto (picture setup), Clock, Phase, H-Position, V-Position, CH Scan, Program, Manual Scan, Update Scan, Channel Edit, Audio (Balance, Bass, Treble, Surround), Language, OSD Background
Picture Mode	Vivid / Movie / Sport / Game / User
Sleep Timer Function	Off / 30 min. / 60 min. / 90 min. / 120 min.
Teletext	1000 pages
Power Supply	AC 100-240 V, 2.4A, 50/60Hz
Power Consumption	Operation ≤ 60W, Standby < 5W
Safety / EMC	TUV-GS / Gost-R / CE / RoHS / WEEE
Accessories	Remote Control, Batteries, User Manual, Power Cord
VESA Mounting	100 x 100 mm
System Dimension / Carton Size	540(W) x 438(H) x 182(D)mm / 578(W) x 500(H) x 112(D) mm
N.W. / G.W.	6.8 Kg / 8.8 Kg

Jupiterstraat 106, 2132 HE Hoofddorp, The Netherlands
TEL +31 (0)23 - 567 10 56 FAX +31 (0)23 - 567 10 67
info@nl-mirai.com

www.mirai.eu